data 2

Data Sheet · Display · Issue April 2003

S5 SILVER LINE
15 inch LCD TFT Display

The extremely flat new 15" TFT monitor from Fujitsu Siemens Computers will captivate you. Not only does this stylish designed monitor offer you the same resolution as a 17 Inch CRT monitor but its extremely flat screen and its removable loudspeakers will particularly suit to please those who keep on high technology combined with exclusive design.

- 15 inch LCD TFT display (TFT with analogue interface)
- High resolution 1024 x 768 pixels
- 16.7 million colors
- Viewing angle 120° horizontal, 100° vertical
- Optimum ergonomics ISO13406-2
- Distortion-free image
- Excellent focus and high contrast
- Low power consumption
- Plug & Play DDC 2B Interface
- Inventory data readable VESA EDID v2.x
- Low-radiation and environmental-friendly according to TCO'99
- Immune to external electromagnetic fields
- 1 video input (D-SUB)
- 7 languages OSD menu
- Mechanical interface standardized to VESA FPMPMI (75 mm)
- Country specific warranty

Data Sheet

www.fujitsu-siemens.com

FUJITSU COMPUTERS SIEMENS

Visible screen diagonal	**15 inch** (38 cm)
Graphics display (dependent on graphics processor)	
Pixels	1024 x 768
Pixels *)	800 x 600
Pixels *)	640 x 480
*)expanded	
Text display (dependent on graphics processor)	
Pixels (max. 75Hz)	720 x 400
Picture size	304 x 228 mm
Frequencies	
Horizontal	30 - 60 kHz
Vertical	56 - 75 Hz
Brightness typical	250 cd/m²
Contrast typical	400:1
Viewing angle typical.	
Horizontal	120°
Vertical	100°
Response time typical	16 ms
Plug & Play	VESA DDC 2B
Setting options	
Brightness & Contrast	
H, V position, H-size, Phase	
Color select	
Auto-adjust	
Reset	
Menu language (7-language)	
OSD position	
Exit	
Tilt base	
Tilt angle	0° - +30°
Audio characteristics	
Audio signal Input	RCA audio L/R
Sound output	3 W (L) + 3 W (R)

Electrical values	
Rated voltage	100-240 V
Frequency	50-60 Hz
Power draw	
Operating typ.	25 W
Off mode typ.	2,5 W
Protection class	1
Temperatures/dimensions/weight	
Ambient temperature (to IEC721)	
Recommended range	15°C to 35°C
Limit	5°C to 35°C
Dimensions (H x W x D)	348 x 351 x 150 mm
Weight	approx. 2,8 kg
Reliability typical	
MTBF (demonstrated)	50,000 h
Lifetime of Backlight (brightness > 50 % of original brightness)	30,000 h
Compliance with standards	
Product safety	EN60950 CB UL1950 CSA 22.2 No.950
Ergonomics	GS mark ISO 13406-2 (pixel faults class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN50024, 61000-3-2/-3); MPR II, TCO'99
Video input	D-SUB 15-pin
Data cable (1.5 m)	D-SUB (15-pin) detachable on monitor
Audio cable (1.5m)	Sound input RCA audio L/R – 3.5 mm stereo phone jack
Power cable (1.8 m)	For wall socket Euro-Schuko-Type CEE7 External power adapter Plug type on power adapter IEC-320-C13
Special features	Standardised mounting interface according, Kensington Lock prepared VESA FPMPMI (75 mm),
Order code	**FSP:** 840 002105 oder S26361-K876-V170

Published by

Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.

Copyright © Fujitsu Siemens Computers, 02/2003

Company stamp